



## **CONTI® SYNCHROFORCE CARBON**

Das Multitalent  
The Allrounder



# CONTI® SYNCHROFORCE CARBON






Hochleistungszahnriemen für hohe Beschleunigungskräfte und Schockbelastungen mit Glas-Carbon-Hybrid Zugstrang.  
Heavy-duty timing belts for high acceleration forces and shock loads with a glass-carbon hybrid tension member.




- Höchstes Leistungsniveau
- Ölbeständig
- Riemengeschwindigkeiten bis 60 m/s
- Elektrisch leitfähig nach ISO 9563
- Beständig gegen extreme Temperaturen von -30°C bis +130°C
- Unrivaled performance level
- Oil-resistant
- Belt speeds up to 60 m/s
- Electrically conductive to ISO 9563
- Resistant to temperature extremes from -30°C bis +130°C

- **Das starke Multitalent für allerhöchste Ansprüche**
- **Multitalented and strong for the most demanding requirements**

## Profil / Profile

HTD	STD	CTD	GTR	HPPD
				
8M	8M	8M	14M*	14M*

\* Auf Anfrage/On request



- |                                 |                                    |
|---------------------------------|------------------------------------|
| Spezial veredeltes Gewebe       | Specially finished fabric          |
| Zähne aus Synthetikgummi        | Synthetic rubber teeth             |
| Glas-Carbon-Hybrid Zugstrang    | Glass-carbon hybrid tension member |
| Riemenrücken aus Synthetikgummi | Synthetic rubber backing           |



The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2017 ContiTech AG. All rights reserved. For complete information go to: [www.contitech.de/disc\\_en](http://www.contitech.de/disc_en)

