



## CONTI® FLUX HOSE - RED

For the safe transport of fluxes and fuel gases



**MARKING:** on red cover "Continental FLUX 6,5 x 12,5 2MPa (20 BAR / 290 PSI) Made in Germany W/J/TC"

### APPLICATIONS

Welding and brazing machines

### FLOW MEDIUM

With fluxed fuel gases (without LPG, MPS, natural gas, Methane)

### DESCRIPTION

- Inner lining:** PA, black, seamless
- Reinforcements:** Synthetic fibres
- Cover:** CSM-BR, red, smooth, ozone-resistant
- Working pressure up to:** 20 bar / 290 psi
- Temperature range:** from -20 °C / -4 °F up to +60 °C / +140 °F
- Further properties:** n-Petan resistance according to DIN EN ISO 3821  
Resistance to glowing particles according to DIN EN ISO 3821

### TECHNICAL DATA

nominal width	inner-Ø	wall thickness	outer-Ø	length	working pressure		min. burst pressure		min. bending radius	weight
Zoll/inch	mm	mm	mm	m	bar	psi	bar	psi	aprx. mm	aprx. g/ m
1/8	3,2	1,9	7	> 10	20	290	60	870	50	36
1/4	6,5	3	12,5	> 10	20	290	60	870	60	97

Temperature resistance applies only to materials used / All technical data apply at room temperature / High pressure and/or temperature lead to reduced component durability