



PARKING®



MARKING: 6 blue stripes on black cover

APPLICATIONS

Compressed air and compressor manufacturers, Largescale garages, Over- and underground workings, Petrol stations, Quarry, Shipyards, Steel and iron industry

FLOW MEDIUM

Compressed air, Pressurized air

DESCRIPTION

- Inner lining:** SBR, black, non-porous, smooth
- Reinforcements:** Synthetic fibres
- Cover:** SBR-EPDM, black, smooth
- Working pressure up to:** 20 bar / 290 psi
- Temperature range:** from -20 °C / -4 °F up to +65 °C / +149 °F
- Further properties:** Suitable for hot water for a short time up to +80°C / +176°F

TECHNICAL DATA

nominal width zoll/inch	inner-Ø mm	wall thickness mm	outer-Ø mm	length m	working pressure		min. burst pressure		min. bending radius aprx. mm	weight aprx. g/ m
					bar	psi	bar	psi		
1/4	6	3,5	13	25	20	290	60	870	60	170
1/4	6	3,5	13	50	20	290	60	870	60	170
1/3	8	3,5	15	25	20	290	60	870	80	200
1/3	8	3,5	15	50	20	290	60	870	80	200
3/8	10	3,5	17	25	20	290	60	870	100	250
3/8	10	3,5	17	50	20	290	60	870	100	250
1/2	13	4,3	21,6	40	20	290	60	870	130	350
1/2	13	4,3	21,6	20	20	290	60	870	130	350
3/4	19	5,5	30	40	20	290	60	870	190	580
3/4	19	5,5	30	20	20	290	60	870	190	580

Temperature resistance applies only to materials used / All technical data apply at room temperature