



TRIX® PAINT SPRAY HOSE NBR

For simple and safe painting



MARKING: 6 grey, axially applied stripes on a black background "Continental TRIX® FARBSPRITZ / PAINT SPRAY NBR DN 9 PN 25 BAR / 363 PSI R < 10⁶Ω Made in Germany"

APPLICATIONS

Coating companies, Painting companies, Shipyards

FLOW MEDIUM

Ammonia solution - 25%, Benzine, Caustic soda - 10%, Distempers, Emulsion paints, Ethyl alcohol, Polyurethane lacquer, Spirit lacquer, Water, Water-based paints

DESCRIPTION

Inner lining: NBR, black, non-porous, smooth

Reinforcements: Synthetic fibres

Cover: NBR, black, smooth, ozone-resistant

Working pressure up to: 25 bar / 363 psi

Further properties: Length independently electrically conductive, Ω-CL (acc. to EN ISO 8031)

Temperature range: from +5 °C / +41 °F up to +35 °C / +95 °F

TECHNICAL DATA

nominal width zoll/inch	inner-Ø mm	wall thickness mm	outer-Ø mm	length m	working pressure		min. burst pressure		min. bending radius aprx. mm	weight aprx. g/ m
					bar	psi	bar	psi		
1/4	6	3.5	13	40	25	363	100	1450	60	170
3/8	9	3.5	16	40	25	363	100	1450	90	230
7/16	11	4	19	40	25	363	100	1450	110	260

Temperature resistance applies only to materials used / All technical data apply at room temperature