



TRIX® SUPER

The high-grade water hose



MARKING: 2 yellow markings on black cover opposite each other * Continental TRIX® SUPER DN 13 PN 30 BAR / 435 PSI Ω-CL Made in Germany*

APPLICATIONS

Agriculture, Construction industry, Foundries, Machinery and plant engineering, Municipal enterprises, Oil and chemicals processing industry, Steel and iron industry

FLOW MEDIUM

Cooling water, Water

DESCRIPTION

Inner lining: EPDM, black, non-porous, smooth

Reinforcements: Synthetic fibres

Cover: EPDM, black, smooth

Working pressure up to: 30 bar / 435 psi

Temperature range: from -40 °C / -40 °F up to +120 °C / +248 °F

Further properties: Length independently electrically conductive, Ω-CL (acc. to EN ISO 8031)

TECHNICAL DATA

nominal width zoll/inch	inner-Ø mm	wall thickness mm	outer-Ø mm	length m	working pressure		min. burst pressure		min. bending radius aprx. mm	weight aprx. g/ m
					bar	psi	bar	psi		
3/8	10	3,5	17	50	30	435	90	1305	35	225
1/2	13	4	21	50	30	435	90	1305	50	315
5/8	16	4	24	50	30	435	90	1305	60	310
3/4	19	4,5	28	50	30	435	90	1305	65	480
1	25	5	35	50	30	435	90	1305	110	650

Temperature resistance applies only to materials used / All technical data apply at room temperature / Definition acc. EN ISO 8031: Ω-CL: R < 10⁶ Ω per assembly (conductive cover & lining) / Ω-C: R < 10⁶ Ω per assembly (conductive cover)